

REQUEST FOR QUOTATION

GENERAL INFORMATION		PR Number	: 2500018235
Validity	:	Quotation Deadline	:
Delivery Time	:	Currency	: VND
Country of Origin	:	Printed by	: LQH8409025
Price	: Exclude VAT	Send Quotation to	: purchasing.mp@semenindonesia.com

Item	Material Code	Description	Qty	UoM	Price per Unit	Amount
1	324-600114	BELT,STEEL CORD:ST1000/6+4,BW1000,DIN-X Belt Conveyor steel cord for long belt from crusher with: Belt type : ST 1000 ; Belt Width : 1000 mm; Safety factor: 5,9 ; Material of cover: Steel cord / Rubber ; Thickness rubber of top : 6 mm; Thickness rubber of bottom cover: 4 mm; Diameter steel cord: 4 mm ; Distance Steel cord center to center: 12 mm (LIKE SAMPLE) ; Distance from steel cord to edge belt conveyor: 26 mm (LIKE SAMPLE) ; Amount / number of steel cord : 79 ; Shore/ Hardness: Shore A (60-65); Tensile strength: 1000 N/mm ; Temperature : Ambient ; Standard: Din-X ; Belt used for Handled material Limestone and clay premix with: - grain sized: 0-80mm - bulk density: 1.3 t/m3 - moisture content-max: 8% ; Warranty 12 month from used (installation) ; Supporting technical to install until run (free)	600,000	M		
			Gross Price exclude VAT :			
Imlementor Note :						
Vendor Note & Signature :			Thang Long Cement JSC			